

Portable Multi Gas Detector

INSTRUMENTS

PONPE 320 Series

Function

- · Intrinsically safe, CE certified
- Portable, industrial use, higher accuracy, Sensitivity and accuracy
- · Imported high quality sensors
- · Detecting multi gas concentrations simultaneously
- · Fully configurable alarm points
- Customized gas combination, private label & logo



Technical Parameters

Sensor type	Infrared, catalytic, electrochemical	Data logging (optional)	Continuously data logging (1900 data at 0.1–10 configurable interval)
Size & weight	130×66×30mm / 300g	Charging time	4-5 hours
Battery	Rechargeable lithium	Continuous working time	>12h
Alarms	LED alarm @ ≥20cm Buzzer alarm ≥95dB @30cm Low power alarm	Working Temperature	-25°C ~ +55°C, short time: -40°C ~ +55°C
Charging	By AC adapter or 5V USB port	Sensor lifetime	Infrared: ≥5 years Electrochemical: ≥2 years Catalytic: ≥1 year
Display	Color LCD / OLCD	Ex proof sign	Exibd I
LCD reading	Real-time concentration, battery indicator, date	Sampling	Natural diffusion
Backlight	Always ON	IP degree	IP54
Approval	Ex, MA, CMC, CE		

Specifications

	Range
Oxygen	(0.00-30.0)%VOL
Carbon Monoxide	(0-1000) ppm
Hydrogen Sulfide	(0-100) ppm
Methane	(0.00-5.00)%VOL
LEL	(0-100)%LEL
Methane	(0.00-4.00)%VOL
Oxygen	(0.0-30)%VOL
Methane	50%LEL
Carbon Monoxide	50%LEL
Carbon Monoxide	(0-1000) ppm
Oxygen	(0.0-30.0)%VOL
02	(0.00-30.0)%VOL
Carbon Dioxide	(0.00-5.00)%VOL
Methane	(0.00-5.00)%VOL
Carbon Dioxide	(0.00-5.00)%VOL
	Carbon Monoxide Hydrogen Sulfide Methane LEL Methane Oxygen Methane Carbon Monoxide Carbon Monoxide Oxygen O2 Carbon Dioxide Methane

Gas Detected	Range
Methane	(0−100)%VOL
Carbon Dioxide	(0−100)%VOL
Hydrogen Sulfide	(0-100) ppm
Methane	(0.00-5.00)%VOL
Carbon Monoxide	(0-1000) ppm
Carbon Dioxide	(0.0-30.0)%VOL
Methane	(0.00-5.00)%VOL
Oxygen	(0.0-30.0)%VOL
Hydrogen Sulfide	(0-100) ppm
Methane	(0.00-5.00)%VOL
Carbon Monoxide	(0-1000) ppm
Hydrogen Sulfide	(0-100) ppm
Carbon Monoxide	(0.00-5.00)%VOL
Oxygen	(0.0-30.0)%VOL
Hydrogen Sulfide	(0-100) ppm
Nitrogen Dioxide	(0-20) ppm
Carbon Dioxide	(0.00-5.00)%VOL
	Methane Carbon Dioxide Hydrogen Sulfide Methane Carbon Monoxide Carbon Dioxide Methane Oxygen Hydrogen Sulfide Methane Carbon Monoxide Hydrogen Sulfide Carbon Monoxide Oxygen Hydrogen Sulfide Carbon Monoxide Oxygen Hydrogen Sulfide Oxygen



Portable Multi Gas Detector

Accessories

Ctandard accordarios	USB extension cord, charging adapter, calibration cap, calibration hose,	
Staridard accessories	stainless steel clip, hanging cord, leather case, manual	
Optional accessories	Cas sampling pump, professional suitcase	

Datalogger (Optional)

Collect data by independent gas detector, there's a chip inside for memory, total data can be collected is 1900pcs, time interval is 1–600 seconds configurable, how to read data? Connect gas detector by USB and read data on computer.

Real-time data collection, connect gas detector with computer for real-time data collection, collected data will be stored on computer, so there's no memory limits.

