

Water Quality Meter

PONPE 519 Series pH/ORP/EC/TDS/Salt/Temp Meter

Features

- · Super large LCD with multiple parameters display
- · Powered by adaptor for continuously using
- Durable electrode holder for left & right side placement
- Measuring stability indicator
- Auto or manual temperature compensation
- Auto ranging or manual ranging
- Up to 5 points calibration points
- Data hold/memory maximum/memory minimum function
- Calibration&electrode information review
- 99 points memeries w/real time stamp
- PC output for data download



















PONPE 519PH | pH/Mv meter PONPE 519PC | pH/Mv/ORP/TDS/Salt meter



Accessories

PONPE 519PH pH/Mv meter

- pH Probe
- adaptor 220v
- CD Software
- · Electrode holder

PONPE 519PC pH/Mv/ORP/TDS/Salt meter

- pH Probe
- EC Probe
- adaptor 220v
- CD Software
- Electrode holder






Water Quality Meter

PONPE 519 Series pH/ORP/EC/TDS/Salt/Temp Meter

Specifications

PONPE 519PH | pH/Mv meter
PONPE 519PC | pH/Mv/ORP/TDS/Salt meter







TDS Factor
Temp. coefficient
Temp. range
Temp. accuracy
Temp. resolution
Compatible probe
LCD size(mm)

Dimension Weight Power

Operating temp.&%RH Storage temp.&%RH

	PONPE 519PH	PONPE 519PC
Т	0.00 ~ 14.00 pH	0.00 ~ 14.00 pH
\perp	±0.02	±0.02
\perp	0.01	0.01
\perp	±1999mV	±1999mV
\perp	\pm 0.2 mV (199.9mV) or \pm 2mV for others	\pm 0.2 mV (199.9mV) or \pm 2mV for others
\perp	\pm 0.1mV (199.9mV) or \pm 1mV (others)	\pm 0.1mV (199.9mV) or \pm 1mV (others)
	N/A	0~19.99, 0~199.9, 0~1999μS/cm; 0~19.99, 0~199.9mS/cm
П	N/A	±1%F.S ±1digit
	N/A	0.05%of FullScale
T	N/A	0~19.99, 0~199.9, 0~1999ppm; 0~19.99, 0~199.9ppt
Т	N/A	±1%F.S ±1digit
Т	N/A	0.05% of Full Scale
Т	N/A	0~11.38ppt , 0~80.0ppt (NaCl)
	N/A	±1%F.S ±1digit
	N/A	0.1
	N/A	0.3~1.00
	N/A	0~10.0%/°C
	0~80.0°C	0~80.0°C
	±0.5°C	±0.5°C
	0.1	0.1
	PH	PH, ORP, COND.
	40x105(HxW)	40x105(HxW)
	0~50°C, Humidity <80%	0~50°C, Humidity <80%
	–20~60°C, Humidity (90%	−20~60°C, Humidity <90%
	260x168x58 (LxWxH)	260x168x58 (LxWxH)
	150g	150g
	9V adaptor	9V adaptor